

New

## AS-Interface Modules (IP30)



Part number: 22260809



정보

- 충분한 산업화

### 장점

- 표준화된 인터페이스
- 자동화 분산을 위한 제품
- 컴팩트한 크기로 공간 절약
- 설치 용이
- 빠르고 쉬운 에러 트래킹

### 응용반경

- 자동화 기술
- 기계 엔지니어링
- 공장 엔지니어링
- 도구 상점
- 자동차 산업

### 제품개요

- AS-인터페이스 모듈 종속장치

- Field bus 활성화와 입출력 레벨의 통합
- 금속 하우징
- 스크류-플러그 터미널이나 스프링 플러그 터미널로 연결
- 센서/액추에이터 연결 위한 디지털 입출력
- LED 진단 및 상태 표시
- 합선 및 과부하 방지

### 승인(규범 참고 자료)



### 적합한 케이블

- UNITRONIC® BUS ASI : 290 페이지
- UNITRONIC® BUS ASI FD : 291 페이지

### Technical data

**Fieldbus system**  
AS-Interface

**Dimensions W x H x D in mm**  
105 mm x 85 mm x 22,5 mm

**Connection type**  
Connector for screw-plug terminals or spring-plug terminals

**Installation**  
DIN rail adapter (35 mm)

**Degree of protection**  
IP30

**Protection class**  
II

**Ambient temperature (operation)**  
-25 °C up to +60 °C

**Ambient temperature (storage/transport)**  
-40 °C up to +85 °C

**Permissible humidity (storage/transport)**  
max. 95 %, not condensing

**Voltage consumption**  
26.5 V DC to 31.6 V DC

Part number	Article designation	Connection method (Sensor/Actuator)	Number of inputs	Number of outputs	Slave type	AS-i specification	Master specification	PU
<b>4 Outputs Relay 3A</b>								
22260807	AB-ASI-DI4DOR4-3A	2, 3-wire	4	4	Single-Slave	3.01	>= 3.0	1
<b>4 Outputs 2A</b>								
22260808	AB-ASI-DI4DO4-2A	2, 3-wire	4	4	Single-Slave	3.01	>= 3.0	1
<b>8 Outputs 2A</b>								
22260809	AB-ASI-DI8DO8-2A	2, 3-wire	8	8	Single-Slave	3.01	>= 3.0	1

Plug terminals are not included, may be obtained as accessory

For detailed information please see the data sheet or installation procedure ([www.lappautomation.com](http://www.lappautomation.com))

### Accessories

- AS-Interface Distributor see page 376
- AS-Interface counter module see page 377
- AS-Interface long distance repeater see page 378
- AS-Interface power supply see page 379
- AS-Interface network extension see page 380
- AS-Interface plug terminals see page 381
- Powerkabel M12 see page 390