



New

M 12 socket with connected master cable



경고

● 연결 체인 적합

M 12 socket with connected master cable

■ 장점

- 4에서 6개의 슬롯이 있는 M8 박스를 위한 연결 케이블
- M 12 연결.

■ 응용반경

- 자동화 기술
- 기계 엔지니어링
- 공장 엔지니어링
- 도구 상점
- 자동차 산업

■ 제품개요

- M12 선에 연결된 이형 소켓으로 설계
- 페인트나 바니쉬로 가릴 수 있는 물질 없음
- 연결 체인 적합

■ 승인(규범 참고 자료)



■ 디자인

- PUR/PVC 케이블
- 영구적으로 유연한 제어 케이블
- 외피 색상 : 검정

■ Technical data



Degree of protection
IP65/IP68/IP69K

Ambient temperature (operation)
Plug/socket

-25 °C to +90 °C

Cable, fixed installation

-40 °C up to +80 °C

Cable, flexible installation

-5 °C up to +80 °C

Contact material

CuZn

Contact surface material

Ni/Au

Coding

A - Standard

Material, knurls

Zinc die-cast, (nickel-plated)

Material of grip body

TPU, hardly inflammable, self-extinguishing

Part number	Article designation	Length in m	Nominal voltage U _N in V	Nominal current I _N in A	PU
8 pole angled socket					
22260615	AB-C8-5,0PUR-M12FA	5	30	2	1
22260616	AB-C8-10,0PUR-M12FA	10	30	2	1

Copper price basis: including; For utilization and definition of „Metal price basis“ and „Metal index“ see Appendix T17

Special cable length on request

For detailed information please see the data sheet (www.lappautomation.com)