




New

## DeviceNet/CANopen Cable, M12 connector on free conductor end



경고

● 선조립된 Device Net/Canopen 신호 케이블

Part number: 22260789

**장점**

- BUS, 센서, 액츄에이터 설치를 위한 저렴하고 효율적인 배선
- 컴팩트한 크기로 공간 절약
- 견고한 디자인
- 표준화된 인터페이스

**응용환경**

- 자동화 기술
- 기계 엔지니어링
- 공장 엔지니어링
- 도구 상점
- 자동차 산업

**제품개요**

- 5극 Device Net / CANopen 실드 케이블
- M12 A코드, 신속잠금 시스템
- 직 소켓이나 직 플러그에 연결된 자유도체 종단 디자인

- 마커 캐리어 있음
- 연결 체인 적합

**승인(규범 참조 자료)**



**디자인**

- PUR, 할로겐 프리 실드 케이블
- 영구적인 유연 제어 케이블
- 구조 (신호선) : 19 x 0,12 mm
- 도체 색상 : 적색 - 검정, 청색 - 백색

**적합한 연결선**

- S/A M12커넥터 조립가능 : 364 페이지
- EPIC 데이터 커넥터 : 320페이지

**Technical data**

<b>IP</b>	<b>Degree of protection</b> IP65 / IP67 / IP69K
<b>0</b>	<b>Ambient temperature (operation)</b> Plug / socket -25 °C to +90 °C Cable, fixed installation -40 °C up to +80 °C Cable, flexible installation -20 °C up to +80 °C
	<b>Contact surface material</b> Ni / Au
	<b>Coding</b> A - Standard
	<b>Material, knurls</b> Zinc die-cast, (nickel-plated)
	<b>Material of grip body</b> TPU, hardly inflammable, self-extinguishing
	<b>External cable diameter</b> 6,7 mm
<b>0</b>	<b>Conductor cross section</b> 0,2 mm <sup>2</sup>
	<b>External sheath, color</b> violett RAL 4001
	<b>Outer sheath, material</b> PUR

Part number	Article designation	Length in m	Nominal voltage U <sub>N</sub> in V	Nominal current I <sub>N</sub> in A	Number of poles	PU
<b>5 pole straight connector</b>						
22260789	AB-DN-M12MS-2,0PUR	2	60	4	5	1
22260790	AB-DN-M12MS-5,0PUR	5	60	4	5	1
22260791	AB-DN-M12MS-10,0PUR	10	60	4	5	1
<b>5 pole straight socket</b>						
22260792	AB-DN-2,0PUR-M12FS	2	60	4	5	1
22260793	AB-DN-5,0PUR-M12FS	5	60	4	5	1
22260794	AB-DN-10,0PUR-M12FS	10	60	4	5	1

Copper price basis: including; For utilization and definition of 'Metal price basis' and 'Metal index' see Appendix T17

Special cable length on request

For detailed information please see the data sheet (www.lappautomation.com)