



New

S/A T-connector M 12 as parallel distributor



정보

- DeviceNet 과 CANopen용



S/A T-connector M 12 as parallel distributor

장점

- PROFIBUS 설치를 위한 저렴하고 효율적인 배선
- 컴팩트한 크기로 공간 절약
- 견고한 디자인
- 표준화된 인터페이스

응용환경

- 자동화 기술
- 기계 엔지니어링
- 공장 엔지니어링
- 도구 상점
- 자동차 산업

제품개요

- 5극 T-커넥터 DeviceNet 과 CANopen
- M12 A코드
- M12 소켓에 M12 플러그 와 M12 소켓 직렬 배선 디자인
- 페인트나 바니쉬로 가릴 수 있는 물질 없

승인(규범 참고 자료)



Technical data

Number of poles	5
Degree of protection	IP65/IP67
Ambient temperature (operation)	Plug/socket -25 °C to +90 °C
Contact material	CuZn
Contact surface material	Ni/Au
Coding	A - Standard
Material, knurls	Zinc die-cast, (nickel-plated)
Material of grip body	TPU, hardly inflammable, self-extinguishing
Sealing material	NBR
Contact carrier material	TPU GF
Nominal voltage U_N	60 V
Nominal current I_N	4 A

Part number	Article designation	Nominal current I _N in A	Nominal voltage U _N in V	Number of poles	PU
22260765	AB-C5-M12T-2XM12FS DN	60	4	5	1

For detailed information please see the data sheet (www.lappautomation.com)

Accessories

- Terminating resistor M 12 for DeviceNet/CANopen/PROFIBUS see page 387