

SKINTOP® SDV-M ATEX / SKINTOP® SDVR-M ATEX



SKINTOP® SDV-M ATEX

■ **Benefits**

SKINTOP® SDV-M ATEX

- Permanent and secure sealing in explosion endangered areas
- Easy assembly
- High degree of protection

SKINTOP® SDVR-M ATEX

- Benefits see SKINTOP® SDV-M ATEX

■ **Application range**

SKINTOP® SDV-M ATEX

- SKINTOP® SDV-M ATEX is used together with SKINTOP® MS-M ATEX and SKINTOP® K-M ATEX types.
- Equipment group II / Category 2G+1D

SKINTOP® SDVR-M ATEX

- SKINTOP® SDVR-M ATEX is used together with SKINTOP® MSR-M ATEX and SKINTOP® KR-M ATEX types.
- Equipment group II / Category 2G+1D

■ **Approvals (Norm references)**



■ **Note**

SKINTOP® SDV-M ATEX

- Outside explosion endangered areas also for use in combination with SKINTOP® ST-M and SKINTOP® MS-M

SKINTOP® SDVR-M ATEX

- Outside explosion endangered areas also for use in combination with SKINTOP® STR-M and SKINTOP® MSR-M

■ **Technical data**

Caution
Installation dimensions and tightening torques see instruction leaflet

On request
Gland and sealing insert, pre-assembled

Material
CR

Degree of protection
SKINTOP® SDV-M ATEX
IP 68 - Sizes M12, M16, M20, M25, M32
IP 66 - Sizes M40, M50, M63
SKINTOP® SDVR-M ATEX
IP 68

Range of temperature
-30°C up to +70°C
short-term up to +90°C

Part number	Part designation / size	Outer-Ø mm from - to	Visible height mm	Pieces / PU
SKINTOP® SDV-M ATEX				
54113002	12 ATEX	-	SDV-M ATEX 3	50
54113012	16 ATEX	-	SDV-M ATEX 3	50
54113022	20 ATEX	-	SDV-M ATEX 3	50
54113032	25 ATEX	-	SDV-M ATEX 3	50
54113042	32 ATEX	-	SDV-M ATEX 4	25
54113052	40 ATEX	-	SDV-M ATEX 4	25
54113062	50 ATEX	-	SDV-M ATEX 4	10
54113072	63 ATEX	-	SDV-M ATEX 4	10
SKINTOP® SDVR-M ATEX				
54113013	16 ATEX	-	SDVR-MATEX 4	50
54113023	20 ATEX	-	SDVR-MATEX 5	50
54113033	25 ATEX	-	SDVR-MATEX 5	50
54113043	32 ATEX	-	SDVR-MATEX 5	25