

SKINDICHT® SHV-M-VITON®



SKINDICHT® SHV-M-VITON®

Benefits

- For high temperatures
- Resistant against oils, solvents, acids and chemicals
- Water pressure-tight
- High strain relief
- Robust

Application range

- Water pressure-tight, high temperature resistant cable gland with special conical VITON® sealing element.
- Brickyard
- Sewage treatment plants
- Car wash site

Approvals (Norm references)



Design

- 1 fitting
- 2 washers
- 3 Viton® sealing cone
- 4 brass cone
- 5 compression screw

Note

- Counter nut to be used SKINDICHT® SM-M

Technical data

Caution
Installation dimensions see Appendix T21

Material
Body: Nickel plated brass
Cone seal: FKM
O-ring: FKM

Degree of protection
IP 68 - 10 bar

Range of temperature
-15°C up to +200°C

Part number	Part designation / size	Clamping range ØF mm	Function thread PG	SW mm	Overall length C mm	Thread length D mm	Clear opening F mm	Pieces / PU
SKINDICHT® SHV-M-VITON®								
52105430	12 x 1,5	3,8 - 4,8	7	14 / 14	26,0	5,0	5	50
52105440	16 x 1,5	4,8 - 5,8	9	18 / 17	27,5	5,0	6	50
52105450	16 x 1,5	5,8 - 6,8	9	18 / 17	27,5	5,0	7	50
52105460	20 x 1,5	5,8 - 6,8	11	22 / 20	31,0	6,0	7	25
52105470	20 x 1,5	6,8 - 8,8	11	22 / 20	31,0	6,0	9	25
52105480	20 x 1,5	8,5 - 10,8	13,5	22 / 22	32,5	6,0	11	25
52105490	20 x 1,5	6,8 - 8,8	13,5	22 / 22	32,5	6,0	9	25
52105500	20 x 1,5	10,8 - 12,8	16	24 / 24	34,5	6,0	13	25
52105510	20 x 1,5	13,8 - 14,8	16	24 / 24	34,5	6,0	15	25
52105520	25 x 1,5	15,8 - 17,8	21	30 / 30	38,0	7,0	18	25
52105530	25 x 1,5	17,5 - 19,8	21	30 / 30	38,0	7,0	20	25
52105540	32 x 1,5	19,5 - 21,8	29	40 / 40	44,5	8,0	22	10

Viton® is a registered trademark of DuPont de Nemours