


**SKINDICHT® CN-M**



SKINDICHT® CN-M

**Benefits**

- For high temperatures
- Resistant against oils, solvents, acids and chemicals
- Sea water resistant
- For high mechanical stress
- Increased corrosion resistance

**Application range**

- Chromium nickel steel cable gland with VITON® seal, specially designed for use under tough conditions.
- Pharmaceutical, petrochemical industry
- Off shore
- Wind energy systems
- Brickyard

**Approvals (Norm references)**



**Design**

- Metric connection thread acc. to EN 50262

**Note**

- Suitable counter nut SKINDICHT® SM CrNi M please see chart

**Technical data**

**Caution**  
Installation dimensions see Appendix T21

**Material**  
Body: Chrome-nickel steel in accordance with DIN, material no. 1.4305  
Seal: FPM  
O-ring: FPM

**IP**  
Degree of protection IP 68

**Range of temperature**  
-25°C up to +200°C

Part number	Part designation / size	Clamping range ØF mm	SW mm	Overall length C mm	Thread length D mm	Pieces / PU
<b>SKINDICHT® CN-M</b>						
52032580	12 x 1,5/1	3,5 - 5	17	27,0	10,0	5
52032590	12 x 1,5/2	5 - 6,5	17	27,0	10,0	5
52032600	12 x 1,5/3	6,5 - 8	17	27,0	10,0	5
52032610	16 x 1,5	8 - 10,5	18	30,0	10,0	5
52032620	20 x 1,5	11 - 15	24	31,0	10,0	5
52032630	25 x 1,5	16 - 20,5	30	36,0	11,0	5
52032640	32 x 1,5	21 - 25,5	36	41,0	13,0	5
52032650	40 x 1,5	28,5 - 33	46	44,0	13,0	1
52032660	50 x 1,5	37 - 42	55	48,0	14,0	1
52032670	63 x 1,5	46 - 52	70	51,0	14,0	1
<b>SKINDICHT® SM CrNi M counter nuts</b>						
52032585	12 x 1,5	-	17	3,0	3,0	10
52032615	16 x 1,5	-	19	3,0	3,0	10
52032625	20 x 1,5	-	24	3,5	3,5	10
52032635	25 x 1,5	-	30	3,5	3,5	10
52032645	32 x 1,5	-	36	4,5	4,5	10
52032655	40 x 1,5	-	46	4,5	4,5	10
52032665	50 x 1,5	-	55	5,5	5,5	10
52032675	63 x 1,5	-	70	6,0	6,0	10

Viton® is a registered trademark of DuPont de Nemours