

**New**

**SKINDICHT® SM-M**

**Application range**

- Needed wherever a gland has to be counter-drilled or thin walled housings only allow through holes.

**Approvals (Norm references)**



**Design**

- Metric connection thread acc. to EN 50262



SKINDICHT® SM-M

**Technical data**

**Material**  
 Nickel-plated brass

Part number	Part designation / size	Thickness in mm	SW mm	Outer Ø mm	Pieces / PU
<b>SKINDICHT® SM-M</b>					
52103000	12 x 1,5	3.0	15	16.5	100
52103010	16 x 1,5	3.0	19	20.9	100
52103020	20 x 1,5	3.5	24	26.4	100
52103030	25 x 1,5	4.0	30	33.0	100
52103040	32 x 1,5	4.0	36	39.6	100
52103050	40 x 1,5	5.0	46	50.6	50
52103060	50 x 1,5	5.0	60	66.0	50
52103070	63 x 1,5	5.0	70	77.0	25
52103071	75 x 1,5	8.0	85	95.0	5
52103072	90 x 2	10.0	102	114.0	1
52103073	110 x 2	12.0	124	135.0	1

**New**

**SKINDICHT® SM-PE-M**



SKINDICHT® SM-PE-M

**Benefits**

- Cutting edges cut through the insulating layer, thus guaranteeing an optimum EMC contact
- Suitable for metric glands used in earthing and EMC applications

**Approvals (Norm references)**



**Design**

- Metric connection thread acc. to EN 50262

**Technical data**

**Material**  
 Nickel-plated brass

**Application range**

- For lacquered, anodised and powder coated housings.

Part number	Part designation / size	Thickness in mm	SW mm	Outer Ø mm	Pieces / PU
<b>SKINDICHT® SM-PE-M</b>					
52103300	12 x 1,5	3.5	15	16.5	100
52103310	16 x 1,5	3.5	19	20.9	100
52103320	20 x 1,5	3.7	24	26.4	100
52103330	25 x 1,5	4.2	30	33.0	50
52103340	32 x 1,5	4.7	36	39.6	50
52103350	40 x 1,5	5.5	46	50.6	25
52103360	50 x 1,5	5.5	60	66.0	10
52103370	63 x 1,5	7.0	70	77.0	10
52103371	75 x 1,5	8.0	85	95.0	5
52103372	90 x 2	10.0	102	114.0	1
52103373	110 x 2	12.0	124	135.0	1