

SKINDICHT® BL-M



SKINDICHT® BL-M

■ **Benefits**

- Used wherever threads previously cut must be closed
- Assembling with screw driver

■ **Application range**

- Machine and apparatus construction
- Drives

■ **Approvals (Norm references)**



■ **Design**

- Metric connection thread acc. to EN 50262

■ **Technical data**



On request
Fitted with FKM O-ring



Material
Blind plugs: Nickel plated brass
O-ring: NBR



Degree of protection
IP 54
IP 68 with O-ring



Range of temperature
With O-ring -30°C up to +100°C
Without O-ring -60°C up to +200°C

Part number	Part designation / size	Outer Ø mm	Pieces / PU
SKINDICHT® BL-M			
52103100	12 x 1,5	14.0	100
52103110	16 x 1,5	18.0	100
52103120	20 x 1,5	22.0	100
52103130	25 x 1,5	28.0	100
52103140	32 x 1,5	35.0	50
52103150	40 x 1,5	44.0	25
52103160	50 x 1,5	54.0	10
52103170	63 x 1,5	70.0	10
SKINDICHT® BL-M with O-ring			
52103105	12 x 1,5	14.0	100
52103115	16 x 1,5	18.0	100
52103125	20 x 1,5	22.0	100
52103135	25 x 1,5	28.0	100
52103145	32 x 1,5	35.0	50
52103155	40 x 1,5	44.0	25
52103165	50 x 1,5	54.0	10
52103175	63 x 1,5	70.0	10
52103190	75 x 1,5	80.0	1