


SKINTOP® MS-M-XL / SKINTOP® MSR-M-XL



SKINTOP® MS-M-XL



SKINTOP® MSR-M-XL

Benefits

SKINTOP® MS-M-XL

- Especially for thick walls
- Maximum reliability
- Optimal strain relief
- Large, variable clamping ranges

SKINTOP® MSR-M-XL

- Benefits see SKINTOP® MS-M-XL

Application range

SKINTOP® MS-M-XL

- With long connection thread for applications involving a thicker wall.

SKINTOP® MSR-M-XL

- With reducing seal insert, to seal cables with smaller outer diameters.

Approvals (Norm references)



Design

- Metric connection thread acc. to EN 50262

Note

- Counter nut to be used SKINDICHT® SM-M
- For suitable accessories see SKINTOP® metric accessories

Technical data

- Caution**
Installation dimensions and tightening torques see Appendix T21
- Material**
Body: Nickel plated brass
Insert: Polyamide
Seal: CR
O-ring: NBR
- Degree of protection**
IP 68 - 10 bar
IP 69 K
- Range of temperature**
-30°C up to +100°C

Part number	Part designation / size	Clamping range ØF mm	SW mm	Overall length C mm	Thread length D mm	Pieces / PU
SKINTOP® MS-M-XL						
53112005	12 x 1,5	3-7	16	32,8	12,0	100
53112015	16 x 1,5	4,5-10	20	37,0	12,0	50
53112025	20 x 1,5	7-13	24	39,5	12,0	50
53112035	25 x 1,5	9-17	29	41,5	12,0	25
53112045	32 x 1,5	11-21	36	48,2	15,0	25
53112055	40 x 1,5	19-28	45	53,5	15,0	10
53112065	50 x 1,5	27-35	54	57,0	15,0	5
SKINTOP® MSR-M-XL						
53112105	12 x 1,5	1-5	16	32,8	12,0	100
53112115	16 x 1,5	2-7	20	37,0	12,0	50
53112125	20 x 1,5	5-10	24	39,5	12,0	50
53112135	25 x 1,5	6-13	29	41,5	12,0	25
53112145	32 x 1,5	7-15	36	48,2	15,0	25
53112155	40 x 1,5	15-23	45	53,5	15,0	10
53112165	50 x 1,5	22-29	54	57,0	15,0	5