


**SKINTOP® MS / SKINTOP® MSR**



■ **Benefits**

**SKINTOP® MS**

- Maximum reliability
- Optimal strain relief
- Large, variable clamping ranges

**SKINTOP® MSR**

- Benefits see SKINTOP® MS

■ **Application range**

**SKINTOP® MS**

- In areas with high demands on special mechanical and chemical stability.
- Chemical industry
- Measurement and control technology
- Machine and apparatus construction
- Plant engineering

**SKINTOP® MSR**

- With reducing seal insert, to seal cables with smaller outer diameters.

■ **Approvals (Norm references)**



■ **Design**

- PG connection thread

■ **Note**

- Counter nut to be used SKINDICHT® SM
- For suitable accessories see SKINTOP® accessories PG

■ **Technical data**

**Caution**  
Installation dimensions and tightening torques see Appendix T21

**Material**  
Body: Nickel plated brass  
Insert: Polyamide  
Seal: CR  
O-ring: NBR

**Degree of protection**  
IP 68 - 5 bar

**Range of temperature**  
-30 °C up to +100 °C

Part number	Part designation / size	Clamping range ØF mm	SW mm	Overall length C mm	Thread length D mm	Pieces / PU
<b>SKINTOP® MS</b>						
52015700	MS 7	2 - 6.5	14	25.0	5.0	100
52015710	MS 9	4 - 8	17	29.0	6.0	100
52015720	MS 11	4 - 10	20	32.0	6.0	50
52015730	MS 13,5	5 - 12	22	34.0	6.5	50
52015740	MS 16	8 - 14	24	35.0	6.5	50
52015750	MS 21	11 - 18	30	40.0	7.0	25
52015760	MS 29	16 - 25	40	48.0	8.0	25
52015765	MS 36	19 - 32	50	62.0	15.0	10
52015766	MS 42	28 - 38	57	62.0	15.0	5
52015767	MS 48	34 - 44	64	62.0	15.0	5
<b>SKINTOP® MSR</b>						
52015770	MSR 7	2 - 5	14	25.0	5.0	100
52015780	MSR 9	2 - 6	17	29.0	6.0	100
52015790	MSR 11	3 - 7	20	32.0	6.0	50
52015800	MSR 13,5	4 - 9	22	34.0	6.5	50
52015810	MSR 16	6 - 13	24	35.0	6.5	50
52015820	MSR 21	8 - 16	30	40.0	7.0	25
52015830	MSR 29	10.5 - 20	40	48.0	8.0	25
52015831	MSR 36	19 - 26	50	62.0	15.0	10
52015832	MSR 42	24 - 31	57	62.0	15.0	5
52015833	MSR 48	28 - 35	64	62.0	15.0	5