


SKINTOP® MS-XL / SKINTOP® MSR-XL



SKINTOP® MS-XL SKINTOP® MSR-XL

Benefits

SKINTOP® MS-XL

- Especially for thick walls
- Maximum reliability
- Optimal strain relief
- Large, variable clamping ranges

SKINTOP® MSR-XL

- Benefits see SKINTOP® MS-XL

Application range

SKINTOP® MS-XL

- In areas with high demands on special mechanical and chemical stability.
- Chemical industry
- Measurement and control technology
- Machine and apparatus construction
- Plant engineering

SKINTOP® MSR-XL

- With reducing seal insert, to seal cables with smaller outer diameters

Approvals (Norm references)



Design

- PG connection thread

Note

- Counter nut to be used SKINDICHT® SM
- For suitable accessories see SKINTOP® accessories PG

Technical data

- Caution**
Installation dimensions and tightening torques see Appendix T21
- Material**
Body: Nickel plated brass
Insert: Polyamide
Seal: CR
O-ring: NBR
- IP**
Degree of protection IP 68 - 5 bar
- Range of temperature**
-30°C up to +100°C

Part number	Part designation / size	Clamping range ØF mm	SW mm	Overall length C mm	Thread length D mm	Pieces / PU
SKINTOP® MS-XL						
52115700	MS 7 XL	2 - 6.5	14	32.0	12.0	100
52115710	MS 9 XL	4 - 8	17	35.0	12.0	100
52115720	MS 11 XL	4 - 10	20	38.0	12.0	50
52115730	MS 13,5 XL	5 - 12	22	39.5	12.0	50
52115740	MS 16 XL	8 - 14	24	40.5	12.0	50
52115750	MS 21 XL	11 - 18	30	45.0	12.0	25
52115760	MS 29 XL	16 - 25	40	52.0	15.0	25
SKINTOP® MSR-XL						
52115770	MSR 7 XL	2 - 5	14	32.0	12.0	100
52115780	MSR 9 XL	2 - 6	17	35.0	12.0	100
52115790	MSR 11 XL	3 - 7	20	38.0	12.0	50
52115800	MSR 13,5 XL	4 - 9	22	39.5	12.0	50
52115810	MSR 16 XL	6 - 13	24	40.5	12.0	50
52115820	MSR 21 XL	8 - 16	30	45.0	12.0	25
52115830	MSR 29 XL	10.5 - 20	40	52.0	15.0	25