

SKINDICHT® SM / SKINDICHT® SM-PE



Benefits

SKINDICHT® SM-PE

- Cutting edges cut through the insulating layer, thus guaranteeing an optimum EMC contact
- Suitable for metric glands used in earthing and EMC applications

Application range

SKINDICHT® SM

- Needed wherever a gland has to be countered or thin walled housings only allow through holes.

SKINDICHT® SM-PE

- For lacquered, anodised and powder coated housings.

Approvals (Norm references)



Design

- PG connection thread

Technical data

Material
Nickel-plated brass

Part number	Part designation / size	Height mm	SW mm	Pieces / PU
SKINDICHT® SM				
52003490	SM 7	2.8	15	100
52003500	SM 9	2.8	18	100
52003510	SM 11	3	21	100
52003520	SM 13,5	3	23	100
52003530	SM 16	3	26	100
52003540	SM 21	3.5	32	50
52003550	SM 29	4	41	50
52003560	SM 36	5	51	25
52003570	SM 42	5	60	25
52003580	SM 48	5.5	64	25
SKINDICHT® SM-PE				
52103200	SM-PE 7	4.7	15	100
52103210	SM-PE 9	4.7	18	100
52103220	SM-PE 11	4.7	21	100
52103230	SM-PE 13,5	4.7	23	100
52103240	SM-PE 16	4.7	26	100
52103250	SM-PE 21	5.2	32	50
52103260	SM-PE 29	5.7	41	50
52103270	SM-PE 36	6.7	51	50