




EPIC® DATA PB Sub-D FC

PROFIBUS Connectors Fast Connect



Info

- New innovative insulation displacement terminals suitable for solid and flexible conductors (90° and 180° versions)
- Versions with 2th Sub-D ports
- Optional with LED diagnostic

Benefits

- Quick installation with Fast Connect ('FC') technology
- Compact design: small space requirements
- No loose parts
- Visual bus connection control
- Terminating resistor (integrated) can be switched

Product features

- Fully compatible with market standard
- Max. transmission rate 12 Mbit/s possible
- Current consumption max. 12,5 mA (with LED 35 mA)
- Supply voltage 4.75 - 5.25 V DC (supplied from the terminal)
- Terminating resistor "ON" - the outbound bus cable is disconnected

Norm references / Approvals

- IEC 61158, IEC 61784
- UL File: E331560

Product Make-up

- D-Sub plug, 9-pin, fixing screws 4-40 UNC
- Improved electromagnetic compatibility (EMC) by metallized housing
- Max. cable outer diameter: 8 mm
- Versions with additional Sub-D interface for programming/diagnostic ('PG')
- LED Version indicate:
bus operation - (green)
station transmission - (blue)
terminating resistor "on" - (orange)

Suitable cables

- Bus system PROFIBUS-DP/FMS/FIP

Suitable tools

- FC STRIP stripping tool refer to page 1002
- Kraftform® adjustable torque screwdriver/ Kraftform Kompakt® Set refer to page 1078

Technical data

	ETIM 5.0 Class-ID: EC001132 ETIM 5.0 Class-Description: D-Sub connector
	Dimensions 95 mm x 70 mm x 17 mm - 35° 72 mm x 40 mm x 17 mm - 90° 70 mm x 35 mm x 17 mm - 180° (LxWxH)
	Connection type Fast Connect
	Protection rating IP20
	Terminating resistor 150 Ω
	Interfaces PROFIBUS station: SUB-D socket, 9-pin PROFIBUS cable: FC standard cable, Ø 0.64 mm
	Permissible ambient conditions Operating temperature: -25°C to +85°C *The max. temperature for UL is 60 °C.

Article number	Article designation	PG-Interface	Diagnostic LEDs	PU
35° cable outlet for solid / 7-wire stranded conductor				
21700511	ED-PB-35-FC	no	no	1
21700513	ED-PB-35-PG-FC	yes	no	1
35° cable outlet for 7-/19-wire stranded conductor				
21700514	ED-PB-35-FC-FLEX	no	no	1
21700515	ED-PB-35-PG-FC-FLEX	yes	no	1
90° cable outlet for solid / 7-/ 19-wire stranded conductor				
21700502	ED-PB-90-FC	no	no	1
21700501	ED-PB-90-PG-FC	yes	no	1
21700547	ED-PB-90-LED-FC	no	yes	1
21700546	ED-PB-90-PG-LED-FC	yes	yes	1
180° (AX) cable outlet for solid / 7-/ 19-wire stranded conductor				
21700544	ED-PB-AX-FC	no	no	1

Photographs are not to scale and do not represent detailed images of the respective products.