



H07ZZ-F

Machines, devices; halogen-free: events, locations with a high density of people and valuable assets



Info

- Public buildings

Benefits

- Broad usages due to halogen-free materials
- According to VDE 0100-711, cables with low smoke emission are required in buildings for exhibitions, shows and stands without a fire alarm system
- Type-compliant versions <HAR>-certified with "<HAR>" testing and certification mark for accelerated granting of approvals if final application of cable is within the European CENELEC area

Application range

- Stage technology
- For mobile equipment and machines
- According to EN 50565-2: In dry, damp and wet rooms as well as for fixed installation e.g. on the plaster
- For buildings or industrial plants with a high density of people or valuable assets

Product features

- Low amount of corrosive gases in the event of fire
- Flame-retardant according to IEC 60332-1-2 and bundle flame test according to IEC 60332-3-24
- Low smokes/low smoke density in the event of fire according to IEC 61034
- Ozone-resistant acc. to EN 50363-6, EN 60811-403, EN 50396-8.1.3

Norm references / Approvals

- <HAR> H07ZZ-F cable type approval according to EN 50525-3-21

Product Make-up

- Strands of bare copper wires
- Core insulation: rubber compound, halogen-free
- Outer sheath: rubber compound, halogen-free

Technical data

Classification
 ETIM 5.0 Class-ID: EC001578
 ETIM 5.0 Class-Description:
 Flexible cable

Core identification code
 Up to 5 cores: colour-coded according to VDE 0293-308, refer to Appendix T9
 From 6 cores: black with white numbers

Conductor stranding
 Fine wire according to VDE 0295
 Class 5 / IEC 60228 Class 5

Minimum bending radius
 4 to 8 x outer diameter (EN 50565-1)

Nominal voltage
 U0/U: 450/750 VAC
 In protected and fixed installations:
 U0/U: 600/1000 V

Test voltage
 2500 V

Protective conductor
 G = with GN-YE protective conductor
 X = without protective conductor

Current rating
 VDE 0298 Part 4
 EN 50565-1 / VDE 0298-565-1

Temperature range
 Static/Moved: -40°C/-5°C ...to +90°C

Article number	Number of cores and mm ² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
H07ZZ-F				
1600810	3 G 1.5	9.2 - 11.9	43.2	125
1600811	4 G 1.5	10.2 - 13.1	57.6	155
1600812	5 G 1.5	11.2 - 14.4	72	190
1600815	14 G 1.5	18.8 - 21.3	201.6	570
1600816	18 G 1.5	20.7 - 26.3	259.2	750
1600820	3 G 2.5	10.9 - 14.0	72	185
1600821	4 G 2.5	12.1 - 15.5	96	235
1600822	5 G 2.5	13.3 - 17.0	120	290
1600823	7 G 2.5	17.1 - 21.8	168	520
1600825	14 G 2.5	22.2 - 25.0	336	860
1600836	4 G 4	14.0 - 17.9	153.6	325
1600837	5 G 4	15.6 - 19.9	192	410
1600841	4 G 6	15.7 - 20.0	230.4	440
1600842	5 G 6	17.5 - 22.2	288	550
1600844	4 G 10	20.9 - 26.5	384	770
1600845	5 G 10	22.9 - 29.1	480	950
1600847	4 G 16	23.8 - 30.1	614.4	1070
1600849	4 G 25	28.9 - 36.6	960	1570
1600851	4 G 35	32.5 - 41.1	1344	2040
1600852	4 G 50	37.7 - 47.5	1920	2810

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.
 Copper price basis: EUR 150 / 100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.

Please find our standard lengths at: www.lappkabel.de/en/cable-standardlengths

Packaging size: coil ≤ 30 kg or ≤ 250 m, otherwise drum

Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).

Photographs are not to scale and do not represent detailed images of the respective products.

Similar products

- H07RN-F refer to page 91
- H07RN-F, enhanced version refer to page 92

Accessories

- SKINTOP® CLICK System
- EASY STRIP stripping and cutting tool refer to page 1004
- PEW 8.87 crimping pliers refer to page 1016
- KS 20 cable shears refer to page 999