



ÖLFLEX® FD 90

Highly flexible, single core cable with PVC insulation and PVC sheath - certified for North America

Info

- Core Line for ordinary duty in power chain applications
- Well-proven and reliable
- AWM certification for USA and Canada



- Benefits**
- Multi-standard certification reduces part varieties and saves costs
 - Multifunctional application possibilities
 - Under consideration of the temperature range also suitable for flexible outdoor use
 - Also suitable for fixed installation where space is limited

- Application range**
- In power chains or moving machine parts
 - For internal wiring of electric and electronic equipment in switch cabinets
 - This cable can substitute multi-core power cables where space requirements or minimum bending radii cause problems
 - Specially designed for power circuits of servomotors driven by frequency converters
 - Test systems in the automotive industry, vehicles and stationary fuel cell systems

- Product features**
- Designed for 5 million alternating bending cycles and travel distances up to 10 meter
 - Flame-retardant according to IEC 60332-1-2 & CSA FT1
 - High oil-resistance
 - Low-adhesive surface

- Norm references / Approvals**
- Based on VDE 0250 / 0285
 - UL-AWM-Style 10107, cRU AWM II A/B FT1 ≥150mm²
 - CSA AWM IA/B IIA/B FT 1 ≤ 120mm²
 - UL File No. E63634
 - For use in power chains: Please comply with assembly guideline Appendix T3

- Product Make-up**
- Extra-fine wire strand made of bare copper wires (class 6)
 - Non-woven wrapping
 - Core insulation: PVC
 - PVC outer sheath, black (RAL 9005)

Technical data

- Classification**
ETIM 5.0 Class-ID: EC000057
ETIM 5.0 Class-Description: Low voltage power cable
- Core identification code**
Black or green-yellow, other colours available on request
- Conductor stranding**
Extra-fine wire according to VDE 0295, class 6/IEC 60228 class 6
- Minimum bending radius**
Flexing: 7.5 x outer diameter
Fixed installation: 3 x outer diameter
- Nominal voltage**
IEC: U₀/U 600/1000 V
UL & CSA: 600 V
- Test voltage**
4000 V
- Alternating bending cycles**
5 mio. cycles
- Temperature range**
Flexing: -5°C to +90°C
Fixed installation: -40°C to +90°C

Article number	Conductor cross-section (mm ²)	Outer diameter (mm)	Core colour	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX® FD 90					
0026600	10	9	green-yellow	96	176
0026601	10	9	black	96	176
0026603	16	10.5	green-yellow	153.6	240
0026604	16	10.5	black	153.6	240
0026607	25	11.8	green-yellow	240	361
0026608	25	11.8	black	240	361
0026610	35	14.2	green-yellow	336	482
0026611	35	14.2	black	336	482
0026613	50	16.2	green-yellow	480	660
0026614	50	16.2	black	480	660
0026616	70	18.3	green-yellow	672	898
0026617	70	18.3	black	672	898
0026619	95	19.8	green-yellow	912	1179
0026620	95	19.8	black	912	1179
0026622	120	23.4	green-yellow	1152	1521
0026623	120	23.4	black	1152	1521
0026625	150	25.1	green-yellow	1440	1739
0026626	150	25.1	black	1440	1739
0026628	185	28.1	green-yellow	1776	2305
0026629	185	28.1	black	1776	2305
0026634	240	31.6	green-yellow	2304	2944
0026635	240	31.6	black	2304	2944
0026640	300	33.5	green-yellow	2880	3545
0026641	300	33.5	black	2880	3545

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.
 Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.
 Please find our standard lengths at: www.lappkabel.de/en/cable-standardlengths
 Packaging size: coil ≤ 30 kg or ≤ 250 m, otherwise drum
 Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).
 Photographs are not to scale and do not represent detailed images of the respective products.

- Accessories**
- SILVYN® CHAIN cable protection and guiding systems