



## ÖLFLEX® FD 90 CY

Highly flexible, screened single core cable with PVC insulation and PVC sheath - certified for North America



**Info**

- Core Line for ordinary duty in power chain applications
- AWM certification for USA and Canada
- EMC compliant copper screening

### Benefits

- Multi-standard certification reduces part varieties and saves costs
- For various applications
- Also suitable for fixed installation where space is limited
- Copper screening complies with EMC requirements and protects against electromagnetic interference

### Application range

- In power chains or moving machine parts
- For internal wiring of electric and electronic equipment in switch cabinets
- Specially designed for power circuits of servomotors driven by frequency converters
- This cable can substitute screened multi-core motor cables where space requirements or minimum bending radii cause problems
- Test systems in the automotive industry, vehicles and stationary fuel cell systems

### Product features

- Designed for 5 million alternating bending cycles and travel distances up to 10 meter
- Flame-retardant according to IEC 60332-1-2 & CSA FT1
- High oil-resistance
- Low-adhesive surface
- EMC-compliant

### Norm references / Approvals

- Based on VDE 0250 / 0285
- UL-AWM-Style 10107, cRU AWM II A/B FT1  $\geq 150\text{mm}^2$
- CSA AWM IA/B IIA/B FT 1  $\leq 120\text{mm}^2$
- UL File No. E63634
- For use in power chains: Please comply with assembly guideline Appendix T3

### Product Make-up

- Extra-fine wire strand made of bare copper wires (class 6)
- Non-woven wrapping
- Core insulation: PVC
- Tinned-copper braiding
- PVC outer sheath, orange (RAL 2003)

### Technical data

**Classification**  
 ETIM 5.0 Class-ID: EC000057  
 ETIM 5.0 Class-Description:  
 Low voltage power cable

**Core identification code**  
 Black, other colours are available upon request

**Conductor stranding**  
 Extra-fine wire according to VDE 0295, class 6/IEC 60228 class 6

**Minimum bending radius**  
 For flexible use:  
 7.5 x outer diameter  
 Fixed installation: 3 x outer diameter

**Nominal voltage**  
 IEC:  $U_0/U$  600/1000 V  
 UL & CSA: 600 V

**Test voltage**  
 4000 V

**Alternating bending cycles**  
 5 mio. cycles

**Temperature range**  
 Flexing:  $-5^\circ\text{C}$  to  $+90^\circ\text{C}$   
 Fixed installation:  $-40^\circ\text{C}$  to  $+90^\circ\text{C}$

Article number	Conductor cross-section (mm <sup>2</sup> )	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
<b>ÖLFLEX® FD 90 CY</b>				
0026651	10	9.7	127.6	227
0026653	16	11.2	186.2	297
0026655	25	12.5	257.8	410
0026657	35	15.1	400.7	607
0026659	50	17.1	554.8	808
0026661	70	19.4	775.6	1081
0026663	95	20.9	1028.1	1382
0026665	120	24.5	1282.4	1752
0026667	150	26.2	1410.4	1924
0026669	185	29.2	1935	2611
0026671	240	32.9	2526	3372
0026673	300	34.8	3128.8	4105

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.  
 Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.  
 Please find our standard lengths at: [www.lappkabel.de/en/cable-standardlengths](http://www.lappkabel.de/en/cable-standardlengths)  
 Packaging size: coil  $\leq 30$  kg or  $\leq 250$  m, otherwise drum  
 Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).  
 DESINA® is a registered trademark of the German Machine Tool Builders' Association  
 Photographs are not to scale and do not represent detailed images of the respective products.

### Accessories

- SKINTOP® BRUSH ADD-ON refer to page 734
- SKINTOP® MS-M BRUSH refer to page 733
- SILVYN® CHAIN cable protection and guiding systems