



ÖLFLEX® CRANE 2S

Flexible at cold temperatures, PVC cables with external steel supporting elements



Info

- Double tensile strength safety
- Teach pad cable

Benefits

- Two steel support elements that are integrated into the outer sheath on opposite sides absorb the tensile forces during operation
- Tensile strength of 2100 N per supporting element

Application range

- For connecting movable control panels and consoles
- As a self-supporting shaft cable; in high rack systems
- Suitable for outdoor applications
- Do not use for lift applications!
- The application profiles for ÖLFLEX® CRANE and ÖLFLEX® LIFT cables can be found in the appendix, selection table A3

Product features

- Flame-retardant according IEC 60332-1-2
- Flexible at low temperatures

Norm references / Approvals

- Based on VDE 0250

Product Make-up

- Strands of bare copper wires
- Special PVC-based core insulation
- Special textile wrapping to improve sliding movement between the sheath and cores
- Special PVC-based outer sheath
- Opposing, integrated steel supporting elements

Technical data

Classification
 ETIM 5.0 Class-ID: EC000104
 ETIM 5.0 Class-Description: Control cable

Core identification code
 Black with white numbers acc. to VDE 0293-1

Conductor stranding
 Extra-fine wire according to VDE 0295, class 6/IEC 60228 class 6

Minimum bending radius
 Flexible use: 20 x outer diameter

Nominal voltage
 U₀/U: 300/500 V

Test voltage
 3000 V

Protective conductor
 G = with GN-YE protective conductor
 X = without protective conductor

Temperature range
 Flexible use: -15°C to +70°C

Article number	Number of cores and mm ² per conductor	Cable Ø (mm)	Distance between strain wires (mm)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX® CRANE 2S					
0027503	8 G 1.5	14.7	20	115	373
0027504	12 G 1.5	16.2	21	172.8	439
0027505	20 G 1.5	20.1	25	288	674

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.
 Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.
 Please find our standard lengths at: www.lappkabel.de/en/cable-standardlengths
 Packaging size: coil ≤ 30 kg or ≤ 250 m, otherwise drum
 Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).
 Photographs are not to scale and do not represent detailed images of the respective products.

Accessories

- EASY STRIP stripping and cutting tool refer to page 1004

ÖLFLEX®
 UNITRONIC®
 ETHERLINE®
 HITRONIC®
 EPIC®
 SKINTOP®
 SILVYN®
 FLEXIMARK®
 ACCESSORIES
 APPENDIX