



NYM-J

Standard cable for plaster, brickwork and immovable concrete

Info

- Standard cable for plaster and brickwork



Application range

- For installation on or under the plaster
- In bricks and concrete, except direct embedding in vibrated or compressed concrete
- In dry, damp or wet interiors
- Also suitable for outdoor use if protected against direct sunlight

Product features

- Flame-retardant according IEC 60332-1-2

Norm references / Approvals

- VDE 0250 Part 204

Product Make-up

- Bare copper wire conductor
- Core insulation: Based on PVC
- Filling compound over the core assembly
- Outer sheath: Based on PVC

Technical data

- Classification**
ETIM 5.0 Class-ID: EC000043
ETIM 5.0 Class-Description: House wiring cable
- Core identification code**
Up to 5 cores: colour-coded according to VDE 0293-308, refer to Appendix T9
From 6 cores: black with white numbers
- Conductor stranding**
Single or multi-wire
≥ 16 mm²: multi-wire
- Minimum bending radius**
Fixed installation: 4 x outer diameter
- Nominal voltage**
U₀/U: 300/500 V
- Test voltage**
2000 V
- Protective conductor**
“J” in NYM-J/Dimension with “G”:
With protection earth PE conductor
“O” in NYM-O/Dimension with “X”:
No protection earth PE conductor
- Temperature range**
During installation: +5°C to +60°C
Fixed installation: -40°C to +70°C

Article number	Number of cores and mm ² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
NYM-J				
1600008	1 G 2.5	6.0	24	60
1600009	1 G 4	6.7	38	85
1600010	1 G 6	7.2	58	105
1600011	1 G 10	8.6	96	160
1600012	1 G 16	9.6	154	220
16000003	3 G 1.5	8.4	43	120
16000013	4 G 1.5	9.2	58	150
16000023	5 G 1.5	9.9	72	175
1600003	7 G 1.5	11.6	101	235
16000213	3 G 2.5	9.6	72	170
16000053	4 G 2.5	10.6	96	210
16000063	5 G 2.5	11.5	120	290
1600071	7 G 2.5	13.7	168	380
16010223	3 G 4	11.3	115	250
16000313	4 G 4	12.7	154	315
16000513	5 G 4	14.0	192	370
16010233	3 G 6	12.8	173	335
16000323	4 G 6	13.8	230	410
16000523	5 G 6	15.5	288	500
16000333	4 G 10	18.0	384	680
16000533	5 G 10	19.5	480	810
16000543	5 G 16	23.0	768	1200
16000353	4 G 25	26.0	960	1500
16000553	5 G 25	28.0	1200	1800

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.
Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.
Please find our standard lengths at: www.lappkabel.de/en/cable-standardlengths
Packaging size: coil ≤ 30 kg or ≤ 250 m, otherwise drum
Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).
Photographs are not to scale and do not represent detailed images of the respective products.

Similar products

- NYY-J, NYY-O refer to page 223
- (N)HXMH refer to page 222

Accessories

- STAR STRIP stripping tool refer to page 1000
- KS 20 cable shears refer to page 999