



ASI Distributor
AS-Interface Distributor



Benefits

- Cost-efficient and rational wiring for AS-Interface installations
- Space-saving due to compact dimensions
- Easy to install

Product features

- Field mountable distributor with flat cable clamp
- On 2 flat cables or straight M 12 socket (A-coded)
- Suitable for drag chains
- Panel mounting
- Rated current ≤ 4 A (H-distributor: $I \leq 8$ A)

Product Make-up

- Wire cross-section: 0,34 mm²
- Colour-code: bn (1), wh (2), bu (3), bk (4)
- Outer sheath: PUR halogen-free, black

Suitable cables

- UNITRONIC® BUS ASI Page 325
- UNITRONIC® BUS ASI FD Page 326

Technical data

- ETIM** ETIM 5.0 Class-ID: EC001604
ETIM 5.0 Class-Description: Fieldbus, decentr. periphery - communication module
- Connection type** Penetration technique for flat cable
- IP** **Protection rating** IP 67 (H-distributor: IP69)
- Ambient temperature (operation)** -25°C to +75°C

Article number	Article designation	Length (m)	PU
Distribution of 1 flat cable on 2 flat cables (H distributor)			
22260802	AB-ASI-J-Y-Y-N		1
on M 12 socket (2-pos.)			
22260800	AB-ASI-J-Y-N-M12FS		1
22260803	AB-ASI-J-Y-N-PUR-1,0-M12FS	1	1
22260804	AB-ASI-J-Y-N-PUR-2,0-M12FS	2	1
Distribution of 2 flat cables on M 12 socket (4-pos.)			
22260801	AB-ASI-J-Y-B-M12FS		1
22260805	AB-ASI-J-Y-B-PUR-1,0-M12FS	1	1
22260806	AB-ASI-J-Y-B-PUR-2,0-M12FS	2	1

Copper price basis: inclusive of copper. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges. Photographs are not to scale and do not represent detailed images of the respective products.

Accessories

- Kraftform® adjustable torque screwdriver/Kraftform Kompakt® Set refer to page 1078